


Secondary Beams

Dan Faircloth
ISIS Low Energy Beams Group Leader
Rutherford Appleton Laboratory













ISIS is used to study everything!























Materials for clean energy











Pollution, energy and the environment





ISIS has many different types of neutron and muon instruments:



20 neutron instruments7 muon instruments

11 neutron instruments (more in the way)




... some are very big


...some are smaller and movable




Each instrument is unique and complex...



HRPD Diffractometer












Basic Layout of ISIS Target Stations




Neutron Instruments




Section view of ISIS TS1 target






Target Reflector And Moderators (TRAM)






SECTION THROUGH UPPER MODERATORS




SECTION THROUGH LOWER MODERATORS





Ambient Water

TS1 Project – Major Refurbishment

New £3.4M 0.5 T 13-piece beryllium reflector











TS2 Cryogenic Moderators



coupled moderator: liquid H₂ @ 20 K 4 Bar





decoupled moderator: solid CH₄ @ 45 K



Choppers- spinning shielding



Choppers- spinning shielding

Fermi (17)

7.3 kg Payload 36,000 rpm ±0.05° Phase Control


Disk (56)

30 kg Payload 20,000 rpm ±0.05° Phase Control


T-Zero (4)

68 kg Payload 10,800 rpm ±0.43° Phase Control










The services trolley moves to position the TRAM for operation or maintenance





TS2 Services Trolley Cooling Plant






















The main remote handling task carried out is CH4 moderator replacement Every 3-4 cycles




Targets also need to be replaced every 4-5 years

TS1 Tungsten
Target #4 on flow
test rig






Underground Tunnel for Removal of Active Components in Transport Flask



View of the TS1 TRAM withdrawn into the RHC

This view is from the north side of the RHC

The reflector top section is rolled forward to expose the Tungsten Target




The target has been disconnected and is being lifted away from its working position



The target being lifted over to the disposal can on the south side of the RHC



Target and can being lowered into the transport flask




Shield plug is lowered onto flask.

After the plug is fitted personnel can approach the loaded flask.



The loaded flask is checked by ISIS Health Physics for external radiation and contamination





Storage flask total weight is 9 Tonnes

Flask is moved on 'MasterMover' powered pallet truck

The loaded flask is lifted out of the tunnel








The loaded flask is transported back to R40 for storage









After work in the RHC is complete the area must be cleared and checked

Personnel can enter the RHC when the TRAM is in the forward position

Full suit, gloves, overshoes and respirator are required for this work






For final disposal the target is transferred to a registered and licenced Type B package and transported to Sellafield the UK's nuclear waste storage facility


More power!

- ISIS 160 kW on target
- More power = more neutrons
- The power must be removed somehow
- SNS Oakridge USA = 1.4 MW









1.4 MW liquid mercury target





Close-up of Damage to Target Inner Window (center of beam entrance area)

Cavitation bubble collapse causes serious damage




solution: fizzy mercury with helium

RR BMB BR RRIAR




ESS currently under construction 3 MW on target!








Even more power!






Tests at CERN


Tungsten powder handling system developed at RAL





Institute of Modern Physics, Chinese Academy of Sciences

10-100 MW!



Muons at ISIS

Target Station 1 Vesuvio Maps Merlin Sandals Mari Alf Engin-X Pearl LOQ HRPD Polaris Emma INES Tosca MuSR Muons Chronus Argus

EC muon facility:

- +ve muons
- Three spectrometers for materials studies

RIKEN-RAL muon facility:

- +ve or -ve muons
- Variable momentum
- Two spectrometers for materials studies
- Low energy muon development
- Other fundamental muon physics experiments

7 muon instruments


ISIS Muon Target


10 mm thick graphite target at 45° to the 800 MeV proton beam

About 5% beam lost.


Diffusion bonded to copper to maximise thermal contact

10 kW maximum heat load






The EC Muon Facility











Radiation Levels







Radiation Hard Magnets





Radiation Hard Magnet Design


- In house concrete magnet design
- Coils Potted in concrete
- Water Cooled













CERN Neutrinos to Gran Sasso (**CNGS**)











Creation of Antiprotons



Target



Magnetic Horn





Simon van der Meer


1960s "current sheet lens" originally for neutrino beams then for antiprotons
1.4 mm Al 400 kA 15 μ s (half-sine)



Magnetic Horn











Beam Separation

FAIR — Facility for Antiproton and Ion Research in Europe


Of the pbar produced 2% are "collectible"




Target



Separator




Beam Separation






Shielding Required




Target station and transport container






- Transport container is placed in front of target station.
- Door of target station and transport container are opened.
- Component is gripped by a quick coupling system.
- Trolley moves the component via rail system into the transport container.
- Doors are closed.

Transport concept



CERN and Fermilab pbar Targets


CERN target (Ir or Cu)








Rotating Fermilab target













Radioactive Ion Beams

A powerful way of studying the atomic nucleus



ISOL vs In Flight Fragmentation


Isotope Separation On Line (ISOL): A production line




Very complicated chains of acceleration and separation have been created

In Flight Fragmentation: Filtering an explosion





ISOL produces very pure beams with "long" half life





RIB Intensity

$$I_{\text{RIB}} = \varepsilon \cdot I_{\text{prod}} = \varepsilon \cdot \int_{\text{target}}^{\square} \sigma(E) \, N_{\text{target}} \, (l) \, I_{\text{primary}} (l) \, dl \qquad \qquad I_{\text{RIB}} \quad \text{- rare ion beam intensity } [\text{s}^{-2}] \\ \varepsilon \quad \text{- overall efficiency} \\ I_{\text{prod}} \quad \text{- pruduction rate of a reaction product} [\text{s}^{-2}] \\ \sigma \quad \text{- reaction cross-section } [\text{barn} = 10^{-24} \text{cm}^2] \\ N_{\text{target}} \quad \text{- target atoms per exposed area} \, [\text{cm}^{-2}] \\ I_{\text{primary}} \quad \text{- primary beam intensity} \\ \varepsilon \quad \text{- excellease} \quad \varepsilon_{\text{ionization}} \cdot \varepsilon_{\text{transport}} \cdot \varepsilon_{\text{cool-bunch}} \cdot \varepsilon_{\text{breeding}} \cdot \varepsilon_{\text{post-accel}}$$

 $\varepsilon_{\rm release}$ - probability of not-decaying during the time of extraction from the target/ion source unit

 $arepsilon_{
m ionization}$ - probability of ionization of desired species by chosen ionization mechanism


 $arepsilon_{
m transport}$ - efficiency of mass selection and transport to experimental setup

 $\varepsilon_{\rm cool-bunch}$ - cooling and bunching efficiency (when applicable)


 $\varepsilon_{
m breeding}$ - charge state breeding efficiency

 $arepsilon_{ ext{post-accel}}$ - post acceleration efficiency






In Flight Fragmentation: common components



In flight fragmentation suitable for very short half life beams



The Super Fragment Separator







FAIR — Facility for Antiproton and Ion Research in Europe













FIRST RARE ISOTOPES
11 December 2021
selenium-84 from a krypton-86 beam.



January 2022 they discovered magnesium-18





Positron Sources

Techniques:

- Radio-isotope source
 - long-lived e.g. 22 Na ($^{\sim}10^6$ e $^{+}$ /s)
 - or beam-induced e.g. ^{13}N ($^{\sim}10^9$ e $^{+}/s$)
- MeV or GeV electron beam
- Gamma ray beam

Positron source for the KEKB and the SuperKEKB in Japan





Target material

Requirements:

High Z (Cross section of Bremsstrahlung $\propto Z^2/A$) High melting point

Tantalum(73Ta),


Tungsten(74W),


Tungsten- rhenium alloy (W-Re)

KEKB, SuperKEKB

Target material: W 14mm ($4\chi_0$)


Primary e- beam energy: 4.0 GeV(KEKB) 3.3GeV(SuperKEKB)





Joining of tungsten crystal to a copper body by a hot isostatic pressing (HIP)

Target destruction limit



After the target destruction occurred at SLAC Threshold: 76 → 35 J/g


KEK Positron Sources


KEKB

Quarter wave transformer matching device Pulse coil: 2.3T @ 10kA

SuperKEKB

AMD Flux Concentrator matching device






50Hz rep rate with a bunch charge of $2.5 \times 10^{10} = 2.5 \times 10^{12} \,\text{e}^{+/\text{s}}$

Adiabatic Matching Device (AMD)

Adiabatic invariance is constant during the motion.

$$\int \sum_{i} p_i dq_i = \frac{\pi p_t^2}{eB}$$



AMD field is produced by a flux-concentrator.

The eddy current is induced in the tapered conductor by a changing magnetic field which is made by the primary coil.

The magnetic field is concentrated due to the tapered shape of the FC head.

adiabatic condition

$$\epsilon = -\frac{\mu p_z}{eB_0} \le 0.5$$


$$p_z \le 17.5 \left[MeV/c \right]$$

$$(B0 = 7.0 [Tesla], \mu = 60[1/m])$$

Transverse acceptance

$$p_{t-max} = \frac{e}{2} \sqrt{B_f B_0} a$$


$$r_{max} = \sqrt{\frac{B_f}{B_0}} a$$



a: Diameter of an accelerator iris

Gamma Ray Undulator Source

Considered primarily for the ILC



Gamma Ray Compton Source

Compton backscabering of a laser beam using an electron beam is used in most intense gamma-ray sources such as ELI-NP.

The laser is typically a YAG laser using one or more high brightness optical cavities





Table 1: CLIC parameters for e+ beam

Parameters	Units	CLIC 3 TeV
Energy	MeV	200
N e ⁺ / bunch	10 ⁹	6.7
N bunches/pulse	-	312
Bunch spacing	ns	0.5
Pulse length	ns	156
Emittance (x,y)	mm.mrad	< 10 000
Bunch length	mm	< 10
Energy spread	%	< 8
Repetition rate	Hz	50


(pre-damping ring)



Future Colliders







Higgs Factory

- China Electron Positron Collider (CEPC)
- 100 km underground circular tunnel
- 240 GeV
- \$6bn
- More than million Higgs bosons in 7 years
- \$6000 per Higgs and one Higgs every 3 mins!



Summary

- Secondary beams are incredibly fascinating
- The work they do moves forward our understanding of the universe
- They are at the extreme limit of our:

Knowledge of physics

Engineering capability

Financial and Political ability

We have only scratched the surface

Thank you for listening Questions?