


EIC Detector R&D Project


Peter Jones, University of Birmingham
Daria Sokhan, University of Glasgow/CEA Saclay



Electron-Ion Collider (EIC)

Overview of the facility

Incorporates the Relativistic Heavy Ion Collider at the Brookhaven National Laboratory (BNL)



Uniqueness

World's first polarised electron, polarised proton/light-ion collider

World's first polarised electron, heavy-ion collider

Overarching science questions

How does the mass and spin of the nucleon arise from its constituents?

What are the emergent properties of dense systems of gluons?

Key features

High Luminosity: 10^{33} – 10^{34} $\text{cm}^{-2}\text{s}^{-1}$

Highly polarised beams: 70%

Wide range of energy: 20-140 GeV


Wide range of ion species: p-U

US DOE Project

Total Project Cost = \$2.4B

Start of Operations in 2032




EIC Science Overview



Mass of the nucleon

Spin of the nucleon

Gluons in nuclei



EIC Recent Timeline

- 2020 Jan – CD-0 Approve Mission Need

BNL chosen to host the facility

- 2021 Mar – EIC Yellow Report published

Ended a 15-month design study that had strong UK involvement and leadership

- 2021 Mar – Call for Detector Proposals

- 2021 Jun – CD-1 Approve Alternative Selection and Cost Range

- 2021 Dec – Submission deadline for Detector Proposals

ATHENA – A Totally Hermetic Electron Nucleus Apparatus

ECCE – EIC Comprehensive Chromodynamics Experiment

CORE – Compact detector for the EIC


UK had strong involvement and leadership in both ATHENA and ECCE

- 2022 Mar – Decision on the Project Detector – ECCE chosen as reference design

Merger of ATHENA and ECCE to form the ePIC detector and collaboration



- 2025 Jan – CD-2 Approve Performance Baseline (Preliminary Design Review)

- 2025 Apr – CD-3 Approve Start Construction (Final Design Review)



EIC Detector Proposals


ATHENA



- New 3T solenoid
- Large bore; optimised performance
- Designed for IP6

Laura Gonella (BHM) – Tracking DWG
 Paul Newman (BHM) – Inclusive PWG
 Daria Sokhan (GLA) – Exclusive/tagging PWG
 Peter Jones (BHM) – Proposal Committee

ECCE





- Existing 1.5T solenoid (BaBar)
- Low-risk; cost effective
- Designed for IP6 or IP8

Nick Zachariou (YRK) – Far Backward DWG
 Claire Gwenlan (OXF) – Inclusive PWG
 Rachel Montgomery (GLA) – Exclusive PWG

UK-led Detector R&D


- ATHENA + ECCE = ePIC: central detector and ancillary detectors




WP2: Timepix

WP3: Polarimetry

ePIC Collaboration



ePIC Collaboration
 500+ Participants
 160+ Institutes
 24 Countries



UK Project Overview

▪UKRI Infrastructure Fund

EIC Detector R&D awarded £2.97m

Duration 2.5 years (Oct 2021 – Mar 2024)

Three detector work packages: [MAPS](#), [Timepix](#), [Polarimetry](#)

Funded institutes: [Birmingham](#), [Brunel](#), [Glasgow](#), [Lancaster](#), [Liverpool](#), [York](#), [STFC DL](#), [STFC RAL \(TD and PPD\)](#)

Current award is a [Preliminary Activity](#) or [Scoping Project](#)

Aims of this phase are:

- (i) Establish/maintain technical and scientific leadership
- (ii) Define the size and scope of the UK's contribution to detector construction

Preparing to submit a [Full Infrastructure Project](#) bid in July 2023

▪Track Record

Collaboration has a strong record in developing detector technologies. Relevant examples include: [ALICE ITS2](#); [ATLAS ITk](#); [CLAS12 Forward Tagger](#); [MAMI nucleon polarimeter](#)

WP1 – MAPS (Birmingham, Brunel, Lancaster, Liverpool, STFC DL, STFC RAL)

▪ Central tracking and vertexing

Approximately 10 m² detector comprising **vertex layers**, **barrel layers** and **disks**

Leadership grows out of UK involvement in the US-funded, **EIC Generic R&D** programme

65 nm MAPS technology driven by physics requirements and validated with simulations

Proposed **ITS3 sensor** meets EIC needs


- **Partnership with CERN** minimises risk

EIC will use same concept for **vertex layers**


- **Wafer-scale, stitched sensors, thinned and bent around the beam pipe**

EIC specific development needed for the **barrel layers and disks**:

- **large area stitched sensor** (not wafer scale), and “conventional” low mass support structures



ALICE-ITS3 development



ePIC-SVT Vertex and Barrel layers



ePIC-SVT Vertex layers

WP1 – Sensor Characterisation

▪ MLR (Q4 2020) – RAL IP Block

Test setup for RAL IP block: functional blocks for high-speed data transmission

Chips bonded to carrier boards at [Birmingham](#) and [Liverpool](#)



RAL chip in new test system by DL/BHAM/LIV

X-ray irradiations carried out at [CERN](#) by [Daresbury](#) (Sep 22)


Tests performed at [Daresbury](#) before/after irradiation; analysis on-going

▪ MLR (Q4 2020) – APTS / DPTS

MLR contains [Analogue Pixel Test Structures \(APTS\)](#) and [Digital Pixel Test Structures \(DPTS\)](#) designed by ITS3 groups

[Birmingham](#) and [Liverpool](#) have bonded chips to carrier boards for ITS3

Both institutes have now received and commissioned APTS test setups




APTS test setup at Liverpool

Expect to receive DPTS test setups for [Daresbury](#) and [RAL](#) in Dec 22.

WP1 – Performance Evaluation

Barrel tracking layers

Evolution of ECCE design with more realistic assumptions on material thickness




For reference 0.05 X/X₀ is equivalent to 50 μm of silicon


1. Outer barrel layers (L3 and L4) require conventional support structures
2. Radial positions adjusted to optimize momentum resolution

Simulation studies

Momentum resolution with updated material fails to meet requirement



After optimization with **B = 1.7 T** field



Demonstrated need for a new solenoid

WP2 – Timepix (Glasgow, STFC DL)

▪ Low- Q^2 tagger with Timepix tracker




We have demonstrated:

1. Strong physics case for low- Q^2 tagger; emphasised by workshop on exotic heavy meson spectroscopy
2. Low- Q^2 tagger needs pixel-based tracking detectors in the beam pipe
3. A calorimeter is not required
4. Acceptable data rate ~ 10 Gbps

JINST paper in preparation with co-authors from far-backward detector working group

Detector prototype design using 4x Timepix3 sensors is well advanced

Figure shows results of thermal modelling



WP3 – Polarimetry (York)

Recoil nucleon polarimeter

Central task to develop polarised active scattering media/detectors

New concept to access polarimetry information from **spin-spin** correlations (rather than diminishing **spin-orbit**)

Use **Chemical HyperPolarisation** (ChHP) of liquid media – involves substrate, catalyst, slowly bubbled para-hydrogen

Prototype tests with **pyradine** (C_5H_5N) look promising

Simulations indicate best to place detector is in front of the Zero Degree Calorimeter



Golden channel: $e^- + {}^{208}Pb \rightarrow J/\Psi + N$

Other EIC work:

ePIC Far-backward DWG – **Zachariou**


Also leading the design of the **electron**

beam luminosity monitor pair spectrometer




International Project Schedule and Full Infrastructure Project

NOTE: US Financial Years (FY) = Oct-Sep




UK-EIC Detector R&D Project

International Project Schedule and Full Infrastructure Project



NOTE: US Financial Years (FY) = Oct-Sep



- UK-EIC Detector R&D Project
- UK-EIC Detector Construction Project

Full Infrastructure Project Bid

- **WP1 – MAPS**: 65 nm (wafer-scale) stitched sensors; developed in partnership with ALICE-ITS3. Build ~33% of central tracker – two barrel layers. Technology already adopted in baseline detector.

Institutes: [Birmingham](#), [Brunel](#), [Lancaster](#), [Liverpool](#), [STFC RAL \(PPD & TD\)](#), [STFC DL](#), [Oxford](#)

- **WP2 – Timepix**: low- Q^2 tagger using pixel sensors in vacuum. Build two tracking stations in far backward region. Detector is baseline. Timepix4 is the preferred technology.

Institutes: [Glasgow](#), [STFC DL](#)

- **WP3 – Polarimetry**: current activity is exploring use of novel polarised scattering media using chemical hyperpolarization. Also, leading design of the baseline electron beam luminosity monitor. Contribution to luminosity monitor plus option to build a polarimeter when technology is proven.

Institutes: [York](#)

- **WP4 (NEW) – Accelerator options**: SRF modules (possibly crab cavities); crab cavity LLRF synchronisation; EO-BPM instrumentation; ERL simulation and design.

Institutes: [CI \(Lancaster, Liverpool, ASTeC\)](#), [JAI \(Oxford, Royal Holloway\)](#) and [STFC DL \(TD\)](#)

- **Estimated total cost**: £30m-£35m



Backup

US Project Overview

▪ Project costs

The accelerator complex and *most* of one detector falls within the scope of the US DOE-funded project (originally \$2.2B; now \$2.4B)

DOE Total Project Cost = \$2,249m

DOE Performance Measurement Baseline = \$1,606m

Contingency = \$2,249 - \$1,606m = \$643m (40%)

▪ Accelerator partnerships ~5-10% in-kind

Project cost = \$1,406m; in-kind contribution = \$70m - \$140m (plus contingency)

▪ Detector partnerships ~30% in-kind (project detector)

GPD estimated cost = \$300m

Project cost = \$200m; in-kind contribution = \$100m (plus contingency)

2 x GPDs and 2nd IR = \$400m-\$500m in-kind contribution

▪ In-kind contributions

Total in-kind contributions = \$170m - \$640m (plus contingency)

For the baseline facility (1 GPD) = \$350m (including contingency)

UK Full Infrastructure Project = £35m (\$42m) ≈ 12% contribution

UK Accelerator Capability

▪ Superconducting RF Systems

Lancaster, Daresbury (TD) and ASTeC

Experience from HL-LHC, ESS and PIP-II



HL-LHC cryomodule at Daresbury

▪ Low-level RF and Feedback

Oxford and Lancaster

Oxford has experience of beam-based feedback for colliders based on beam offsets post-IP


Lancaster has experience of RF interferometers for RF synchronization in crab cavities

EIC crabbing system will need both

▪ Electro-optic beam position monitors

Royal Holloway

Building on experience from HL-LHC, these unique devices are capable of measuring crabbing angle on proton or ion beams



▪ ERL modelling and design

Lancaster and Liverpool

Have been studying ERL filling pattern effect on RF and beam stability

Only study of its type; most assume all bunches are identical

We show the differences are critical

EIC Project News

■ US Project Funding


Now on a firmer footing due to **Inflation Reduction Act (IRA)**

Settlement of **\$217m** to **DOE/NP**, of which **\$138m** awarded to **EIC** in **FY23**

IRA funds need to be spent by **FY27**; does not increase the Total Project Cost

Updated project schedule (next slide) – expect **CD-2/3A** review in **October 2023**

■ EIC Funding Profile



Note: RHIC Operations stop in FY25, which coincides with CD-3: Approve Start Construction