



Progress on Muon Cooling




Chris Rogers*, ISIS Neutron and Muon Source,
*chris.rogers@stfc.ac.uk



Progress on Muon Cooling Demonstration


- Muon production
 - Target and transverse capture
 - Beam cleaning
 - Longitudinal capture
 - Charge separation
 - First cooling
 - Bunch merge
 - Second cooling
 - Final cooling
 - Reacceleration
- Complex system
- Requires demonstration of key component – ionisation cooling
 - Focus for this talk will be ionisation cooling

Ionisation Cooling



- Beam loses energy in absorbing material
 - Absorber removes momentum in all directions
 - RF cavity replaces momentum only in longitudinal direction
 - End up with beam that is more parallel
- Multiple Coulomb scattering from nucleus ruins the effect
 - Mitigate with tight focussing \rightarrow low β
 - Mitigate with low-Z materials
 - Equilibrium emittance where MCS cancels the cooling
- Verified by the Muon Ionisation Cooling Experiment (MICE)



6D Ionisation Cooling




- Initial beam is narrow with some momentum spread
 - Low transverse emittance and high longitudinal emittance
- Beam follows curved trajectory in dipole
 - Higher momentum particles have higher radius trajectory
 - Beam leaves dipole wider with energy-position correlation
- Beam goes through wedge shaped absorber
 - Beam leaves wider without energy-position correlation
 - High transverse emittance and low longitudinal emittance
- Tests done at Fermilab




Cooling for a Muon Collider




“MICE-like”



Rectilinear B (Stage B8)




Rectilinear Lattice





- Challenges
 - Dispersion and closed orbit control for 6D cooling
 - Successful RF operation and suppression of RF breakdown
 - Maintaining adequate acceptance between stop bands
 - Magnet engineering
 - Integration of magnet with RF and absorber
 - Day-to-day operation and instrumentation
- Also intensity/collective effects → proton beam test?
 - Space charge, beam loading, absorber/RF window heating
 - Decay radiation load on magnets

Demonstrator Layout



Comparison with Existing Data




	MICE	Demonstrator
Cooling type	4D cooling	6D cooling
Absorber #	Single absorber	Many absorbers
Cooling cell	Cooling cell section	Many cooling cells
Acceleration	No reacceleration	Reacceleration
Beam	Single particle	Bunched beam
Instrumentation	HEP-style	Multiparticle-style

CERN Siting Options




- C/O Roberto Losito



Layout - 10 kW option



Preliminary optics layout


- Preliminary optics layout seems okay
 - Still work in progress
- Dipoles
 - ~ 0.7 T, 30°
 - 0.5 m long
- Quads
 - ~ 1 T/m, TBC
 - 0.5 m long
- Approx 1.5m by 4m region for beam stop
- Followed by beam preparation system






- New site compatible with nuSTORM
 - Measurement of neutrino scattering cross sections
 - Beyond Standard Model physics programme
 - Muon beam test area for Demonstrator
- Demonstration of highest-current high-energy muon beam facility
 - Pion beam handling
 - Target concepts can be tested
 - FFA storage ring → rapid acceleration concepts

Layout - nuSTORM (2)



Beam preparation system

- ~ 100 ps pulsed muon beams don't exist
 - Muons have only rarely been accelerated in conventional RF cavity
 - Low emittance muon beam challenging to achieve
- Need to consider a system to prepare the muon beam
 - Assume momentum collimation in switchyard
 - Transverse collimation
 - Longitudinal phase rotation



Beam Preparation System


Parameter	Value
Cell length	1 m
Peak solenoid field on-axis	0.5 T
Collimator radius	0.05 m
Dipole field	0.67 T
Dipole length	1.04 m
RF real estate gradient	7.5 MV/m
RF nominal phase	0° (Bunching)
RF frequency	704 MHz

Cooling System

Cell length	2 m
Peak solenoid field on-axis	7.2 T
Dipole field	0.2 T



Preliminary Cooling Cell Concept

2 m





RF real estate gradient	7.5 MV/m
RF nominal phase	0° (Bunching)
RF frequency	704 MHz

Cooling System	
Cell length	2 m
Peak solenoid field on-axis	7.2 T
Dipole field	0.2 T
Dipole length	0.1 m
RF real estate gradient	22 MV/m
RF nominal phase	20°
RF frequency	704 MHz
Wedge thickness on-axis	0.0342 m
Wedge apex angle	5°
Wedge material	LiH







Optics vs momentum



- Acceptance driven by tune consideration
 - Tune = number of focusing oscillations per magnetic cell
 - Acceptance for tune near to resonances



Dipole configuration



■ Two possible dipole configurations

- + + + + +
- + - - + +

Dipole configuration




- + - - + yields much more dispersion
- Can create considerably more 6D cooling
- Cost is more non-linearity
 - Challenging to match

Integration issue: RF

- B-fields reduce RF Safe Operating Gradient (SOG)
 - e⁻ emitted from copper
 - B-field focuses on far wall
 - Induces sparks
- Muon cooling needs high RF gradient + B-field
- Two routes demonstrated
 - Either: Beryllium window resistant to damage
 - Or: High-pressure gas absorbs spark
- Other ideas
 - Operate at IN2 temperature
 - Short RF pulse to limit heating

Window material	B-field (T)	SOG (MV/m)
Cu	0	24.4 ± 0.7
Cu	3	12.9 ± 0.4
Be	0	41.1 ± 2.1
Be	3	> 49.8 ± 2.5
Be/Cu	0	43.9 ± 0.5
Be/Cu	3	10.1 ± 0.1


Bowring et al



Yonehara et al


Be RF & LiH Performance

- Use Beryllium for RF cavity walls
- Use LiH in absorber
- Good cooling performance
 - Transverse and longitudinal emittance reduced by $\sim 20\%$
 - Approx factor two reduction in 6D emittance
- Optimisation ongoing
 - Assumes perfect matching for now



Transmission losses	2.00%
Decay losses	4.00%
Trans ε in	1.95 mm
Trans ε out	1.57 mm
Long ε in	3.61 mm
Long ε out	2.99 mm
6D ε in	12.7 mm ³
6D ε out	6.3 mm ³



Demonstrating full cooling performance



0.1663 MV/cm for He at STP


- Cooling scales with dp/p
- Higher energy \rightarrow more RF
- Lowest energy beams \rightarrow muSR

Demonstrating full cooling performance



- Longitudinal only simulation!
 - About 12 % of the muon beam ends up in the low energy bucket (assume uniform incident beam in energy)
 - After 1 metre of cooling system

Timeline



- Assumes full effort of major lab e.g. CERN, Fermilab

- Demonstration of cooling is a key technology requirement for Muon Collider
 - Improved demonstrator lattice studied
 - Beam preparation system looks okay
 - Looking at layout from target to cooling system for CERN site
 - Happy to look at non-CERN sites!
- Aim is to deliver a design by 2026
 - In time for next European strategy update